



## LS5-R22-100g/y

High sensitivity NIDR Single Channel R22 refrigerant gas detector

---

### Product highlights

0-99.9 g/y leak rate range


Single channel detector for highest sensitivity

Easy to integrate in OEM systems

### Applications

HVAC leak detection

## Mechanical drawing



## Operative Data

|                                    |   |
|------------------------------------|---|
| <b>Sensor type</b>                 | Single channel NDIR detector (LS-series)                    |
| <b>Detected gas</b>                | HCFC Refrigerants   |
| <b>Measuring range</b>             | 0 ÷ 99.9 g/y  |
| <b>Operating temperature range</b> | 0 ÷ 55 °C (non-condensing)                                  |
| <b>Storage temperature range</b>   | -20 ÷ 85 °C   |
| <b>Operating humidity range</b>    | 0 ÷ 90 % (non-condensing)                                   |
| <b>Gas supply</b>                  | Flowing (nearly atmospheric pressure)                       |
| <b>Flow rate</b>                   | 120 sccm (for a correct leak rate measure)                  |
| <b>Warm-up time</b>                | < 60 s (start-up time)<br>< 30 minutes (full specification) |

## Mechanical & Electrical Specifications

|                                |  |
|--------------------------------|--|
| <b>Dimension (L x W x H)</b>   | 160mm x 30mm x 40mm                        |
| <b>Weight</b>                  | 155 g                                      |
| <b>Gas connector</b>           | Rapid fitting for 3mm o.d. tubing          |
| <b>Voltage supply</b>          | 5V ± 10%                                   |
| <b>Current consumption</b>     | 110mA (rms) – 220mA (peak)                 |
| <b>Signal Output</b>           | 0-3.3V                                     |
| <b>Communication Interface</b> | UART (Baud-rate: 9600-115200) <sup>1</sup> |

<sup>1</sup> ASCII Protocol described in the LS-series user manual. Default baud-rate is 9600.

## Measuring Specifications

|                              |   |
|------------------------------|---|
| Data rate                    | 2/s                                       |
| Response time T90 (0 – 90 %) | 1 s                                       |
| Resolution                   | 0.1 g/y                                   |
| Repeatability                | ± 0.3 g/y                                 |
| Lower Detection Limit (LDL)  | 0.4 g/y                                   |
| H2O vapor influence          | None                                      |
| Cross-sensitivity            | Other refrigerant gases (contact factory) |